

- CSA approved
- D&L Tanks meet and exceed CSA requirements
- D&L Fibreglass tanks are manufactured with high quality resins and fibreglass
- We do not use fillers in the production of our tanks, producing a tank with higher glass content (superior strength) than tanks produced with ‘filled resin’.
- Our Bonded Unibody design is leakproof and provides increased structural strength and toughness.
- Leakproof bonded 30” manhole for easy entry.
- All tanks are warranted for up to **10 years** with an optional warranty for up to 15 years available for a small additional cost.
- Sizes available from 750 gallon (2,812 litre) to 14,000 gallon (63,600 litre)

At D&L, our commitment to the use of high quality materials and meticulous workmanship is your assurance that your D&L tank will provide many years of trouble-free service.

As a family owned and operated company, we take extreme pride in producing our products to the highest standards.

Need more information? Please visit our website at www.dlproducts.ca

Or contact us and we would be happy to answer any questions you may have regarding our products.

**Now Serving
Saskatchewan through
our Davidson, SK
fabrication plant!**

D&L Fiberglass Products Ltd.

Lot 3 Railway Street
Davidson, Saskatchewan

Phone: (306) 561-7652

www.dlproducts.ca

email: joel@dlproducts.ca



D&L Fiberglass

*Manufacturer of Superior
Quality Fibreglass tanks for
the Water and Sewer
Industry*

D&L Fiberglass Products Ltd.

Lot 3 Railway Street
Davidson, Saskatchewan

Phone: (306) 561-7652

www.dlproducts.ca

email: joel@dlproducts.ca

Superior Quality

From our smallest 750 gallon to our largest 14,000 gallon, our skilled team of fiberglass technicians use only high quality unfilled polyester resin and fiberglass to produce your tank.

Some tank manufacturers use “Wide Spec” or “B-Grade” resins to save money. These resins are available from resin manufacturers when they have a batch that doesn’t meet their quality control standards. B-grade resins are sold “As-Is” without any guarantee as to their strength or cure rate. At D&L, we only use A-Grade Premium resins in our production.

Unibody Design

Our bonded Unibody design ensures a leakproof tank with superior structural strength.

Some Manufacturers of Fibreglass tanks use gaskets, flanges, and bolts to assemble their tanks. At D&L, we bond the tank components together with the same top quality polyester resins and fiberglass that the parts are fabricated from, resulting in a completely sealed, structurally superior seamless tank. Our process of bonding the tanks eliminates the chance of gasket failures.



Not all “Fibreglass” is the same

Information you need to know when choosing a fibreglass tank

Filled vs Unfilled Resins

At D&L, we manufacture all of our fiberglass composite tanks using top quality raw materials. We do not use fillers in the production of our products. “Filled” resin is used by some manufacturers in order to reduce to cost of the materials. This process involves mixing calcium carbonate dust into the resin. While inexpensive, this dust reduces how much fiberglass the resin can saturate, so the finished part contains less fiberglass. Lower fiberglass content results in a less tough, more brittle part.

At D&L, we do not “fill” our resin. This results in a finished product with high fiberglass content for maximized strength, toughness, and durability.

CSA Approved

Our tanks meet and exceed CSA requirements



Bonded Manhole

Our bonded 30” entry provides a leakproof seal and easy access.

